



# CCR K Classic

Durable RFID Reader with  
RGB Keypad for Two-Factor  
Authentication

**CCR K Classic is an exceptionally durable device** with a backlit RGB keypad, designed to **withstand even the harshest conditions** both indoors and outdoors.

RS 485 communication combined with the OSDP™ protocol ensures reliable connectivity with third-party access control, attendance, or dining management systems.

It supports two-factor authentication using a PIN or GIN code, ensuring a high level of security. **The motion sensor with a door open button function** allows the reader to be used in various opening modes (entry-exit).

In attendance systems, it enables the entry of work codes and departments, simplifying employee management.

**CCR K Classic provides a high level of security** and meets cybersecurity requirements, making it an ideal solution for demanding operations.



## FEATURES

- > Highly secure RFID card reading: supports MIFARE® DESFire® Proximity, HID cards and NFC\*
- > RFID card or code identification
- > Backlit mechanical buttons with tactile feedback
- > **Motion sensor** (touchless button on request)
- > Status indication via LED lights
- > RFID readers are designed, developed and manufactured by CONTAL OK

\* HW ready

**CONTAL OK**

contal@contal.sk | +421 41 5052 111

[www.contal.sk/en](http://www.contal.sk/en)

# CCR K Classic

## TECHNICAL SPECIFICATIONS

Operating Frequency	13.56 Mhz 125 kHz Proximity version
Power Supply	10-30 VDC
Current Consumption	Typical 55 mA, Max. 100mA
Protection Rating	IP40 IP65 with installation KIT IP65
Operating Temperature	-40 °C to +55 °C
Keyboard	12 buttons with configurable backlighting
Optical indication	Configurable LED modules
Acoustic indication	With OSDP protocol or via Wiegand input
Dimensions	134 x 74 x 30 mm
Weight	160 g
Color	Black

## SPECIFICATION

Certification	CE Mark
Communication	RS 485 with OSDP protocol
Reading Distance	30 mm
Wall Contact	Yes
Material	ASA-thermoplastic



### Product Code:

**64283031** MIFARE/DESFire 13,56 MHz

**64284031** Proximity 125 kHz

**64285031** HID 125 kHz



**CONTAL OK**

contal@contal.sk | +421 41 5052 111

[www.contal.sk/en](http://www.contal.sk/en)